

## ▼ JHA Series, Aluminium Jacks



Rated Pressure: 70MPa

Rated Tonnage: 7 -100ton

Stroke Range: 76-155mm

- The JHA series products are made of aluminum alloy with a sandblasted and anodized outer surface, resulting in lightweight construction, significantly improved corrosion resistance, and effectively extended equipment lifespan.
- External pressure relief valve to prevent equipment overload
- Precision-machined front and rear surfaces, suitable for confined spaces
- Gas nitriding treated plungers offer higher strength, stronger corrosion resistance, and longer service life
- Standard operating handle
- 7-ton, 15-ton, and 35-ton JHA series products support all-around operation



**Hydraulic Lifter & Track Jack**  
Designed for the initial few centimeters of lifting before full load engagement, making it an ideal tool for lifting applications. The LW-16 Hydraulic Lifter requires a minimum installation clearance of only 10 mm.

## ▼ JHA Model Specifications

Type	Jack Capacity ton(kN)	Stroke (mm)	Model	Effective Piston Area(cm <sup>2</sup> )	Retracted Height (mm)	Extended Height (mm)	Base Size W×L(mm)	Plunger Diameter (mm)	Pump Speed	Weight (kg)
Aluminium Jacks	7 (62)	76	JHA-73	9.6	133	209	73 × 158	30.2	Single Speed	5.0
	15 (133)	153	JHA-156	20.3	247	401	92 × 238	41.4	Single Speed	13.2
	35 (311)	155	JHA-356	45.6	257	412	117 × 254	54.1	Single Speed	18.1