

# Wheeled Lifting Jack

## ▼ WLJ Wheeled Lifting Jack



Capacity: 60-200Ton

Stroke: 350-700mm

Maximum Pressure: 70MPa

- All cylinders adopt gas nitriding surface treatment for high corrosion resistance.
- Double-acting lock nut cylinders ensure safe and reliable operation.
- The lock nut is equipped with 4 manual levers for easy operation.
- Equipped with a spherical saddle and two extension rods of different lengths.
- Enlarged welded base ensures stability, suitable for off-road and unpaved surfaces.
- Covers various tonnage requirements from 60 tons to 200 tons.
- Equipped with a 10-meter manual or pneumatic remote control handle.
- Integrated design of pump body, oil tank and cylinder mounting base for stable structure.
- Electric pump, pneumatic hydraulic pump or lithium battery pump can be selected as power source.
- Equipped with solid rubber wheels, maintenance-free.
- Adjustable-angle transport handle for convenient packaging and transportation.

## ▼ WJL Specification Table

Model	Capacity (Ton)	Stroke (mm)	Pump	Collapsed Height(mm)	Rod A(mm)	Rod B(mm)	MAX advanced height (mm) (no rod/rod A/rod B)
WLJ60350E	60	350	HE4 electric pump	600	100	200	950/1050/1150
WLJ60350A	60	350	HA5 air driven pump	600	100	200	950/1050/1150
WLJ60350B	60	350	BPD battery pump	600	100	200	950/1050/1150
WLJ60700E	60	700	HE4 electric pump	950	200	400	1650/1850/2050
WLJ60700A	60	700	HA5 air driven pump	950	200	400	1650/1850/2050
WLJ60700B	60	700	BPD battery pump	950	200	400	1650/1850/2050
WLJ100400E	100	400	HE4 electric pump	660	100	200	1060/1160/1260
WLJ100400A	100	400	HA5 air driven pump	660	100	200	1060/1160/1260
WLJ100400B	100	400	BPD battery pump	660	100	200	1060/1160/1260
WLJ100700E	100	700	HE4 electric pump	960	200	400	1660/1860/2060
WLJ100700A	100	700	HA5 air driven pump	960	200	400	1660/1860/2060
WLJ100700B	100	700	BPD battery pump	960	200	400	1660/1860/2060
WLJ150400E	150	400	HE4 electric pump	660	100	200	1060/1160/1260
WLJ150400A	150	400	HA5 air driven pump	660	100	200	1060/1160/1260
WLJ150400B	150	400	BPD battery pump	660	100	200	1060/1160/1260
WLJ150700E	150	700	HE4 electric pump	960	200	400	1660/1860/2060
WLJ150700A	150	700	HA5 air driven pump	960	200	400	1660/1860/2060
WLJ150700B	150	700	BPD battery pump	960	200	400	1660/1860/2060
WLJ200400E	200	400	HE4 electric pump	660	100	200	1060/1160/1260
WLJ200400A	200	400	HA5 air driven pump	660	100	200	1060/1160/1260
WLJ200400B	200	400	BPD battery pump	660	100	200	1060/1160/1260
WLJ200700E	200	700	HE4 electric pump	960	200	400	1660/1860/2060
WLJ200700A	200	700	HA5 air driven pump	960	200	400	1660/1860/2060
WLJ200700B	200	700	BPD battery pump	960	200	400	1660/1860/2060